

H series gas engines and gen-sets natural gas

1,200/1,500/1,800 rpm



G-24HM & G-42HM

Engine Parameters ²⁾	English Units	Metric Units	G-24HM				G-42HM			
			1,500		1,800		1,500		1,800	
Speed	rpm									
Engine power ²⁾	bhp	kWb	697	(520)	697	(520)	1,395	(1,040)	1,395	(1,040)
Cylinder arrangement	in Line 8				V12					
Mean effective pressure	psi	bar	252	(17.4)	210	(14.5)	286	(19.7)	238	(16.4)
Bore	inch	mm	5.98	(152)	5.98	(152)	6.30	(160)	6.30	(160)
Stroke	inch	mm	6.50	(165)	6.50	(165)	6.89	(175)	6.89	(175)
Displacement	cu.in	liters	1,460	(24.0)	1,460	(24.0)	1,718	(42.2)	1,718	(42.2)
Mean piston speed	in/s	m/s	325	(8.3)	390	(9.9)	344	(8.8)	413	(10.5)
Compression ratio	11.8:1				11.9:1					
Combustion air mass flow	lbs/hr	kg/h	4,343	(1,970)	5,313	(2,410)	10,516	(4,770)	10,670	(4,840)
Packaged ventilation air flow ³⁾	scfm	m ³ /h	21,424	(36,400)	21,424	(36,400)	42,849	(72,800)	42,849	(72,800)
Engine coolant capacity (Main circuit) ⁴⁾	gal.	liters	21	(80)	21	(80)	63	(240)	63	(240)
Engine coolant capacity (Aux. circuit) ⁴⁾	gal.	liters	5	(20)	5	(20)	20	(75)	20	(75)
Lube oil capacity ⁵⁾	gal.	liters	45	(169)	45	(169)	107	(403)	107	(403)
Lube oil consumption ⁵⁾	lbs/bhp.hr	g/kWh	0.00058	(0.35)	0.00058	(0.35)	0.00025	(0.15)	0.00025	(0.15)

1) Natural Gas MN80. For other MN consult Guascor Energy

2) Engine performance data acc. to ISO 3046/1

3) Assumes intake air flow at delta T = 5°C including combustion air

4) Not including pipes and heat exchangers

5) Mean lube oil consumption between maintenance steps

6) At 60 Hz, U = 0.48 kV, power factor = 1

7) At 50 Hz, U = 0.4 kV, power factor = 1

8) With a tolerance of + 5 %

9) Lower emission engines are available, consult Guascor Energy for performance data

Data is for continuous rating, at sea level, and at an ambient temperature of 77F (25°C)

Data for special gas and dual gas operation on request.

The values given in this data sheet are for information purposes only and not binding.

G-24HM & G-42HM

Energy Balance	English Units	Metric Units	G-24HM		G-42HM	
Generator efficiency ^{6) 7)}	%	%	96.4	96.2	97.2	96.7
Electrical power ^{6) 7)}	kWe	kWe	501	500	1,011	1,006
Jacket (HT) water heat	Btu x 1,000/hr	kW	816.0 (239)	710.2 (208)	1,877.9 (550)	2,000.9 (586)
Intercooler (LT) water heat	Btu x 1,000/hr	kW	280.0 (82)	338.0 (99)	215.1 (63)	204.9 (60)
Exhaust heat - cooled to 120°C	Btu x 1,000/hr	kW	829.7 (243)	997.0 (292)	1,628.7 (477)	1,837.0 (538)
Engine radiation heat	Btu x 1,000/hr	kW	95.6 (28)	136.6 (40)	239.0 (70)	239.0 (70)
Generator radiation heat	Btu x 1,000/hr	kW	63.9 (19)	67.5 (20)	99.4 (29)	117.2 (34)
Fuel consumption ⁸⁾	Btu x 1,000/hr	kW	4,008.5 (1,174)	4,216.8 (1,235)	8,027.3 (2,351)	8,351.7 (2,446)
Mechanical efficiency	%	%	44.3	42.1	44.2	42.5
Electrical efficiency	%	%	42.7	40.5	43	41.1
Thermal efficiency	%	%	48.0	48.5	46.4	48.4
Total efficiency	%	%	90.7	90.6	89.4	89.5

1) Natural Gas MN80. For other MN consult Guascor Energy

2) Engine performance data acc. to ISO 3046/1

3) Assumes intake air flow at delta T = 5°C including combustion air

4) Not including pipes and heat exchangers

5) Mean lube oil consumption between maintenance steps

6) At 60 Hz, U = 0.48 kV, power factor = 1

7) At 50 Hz, U = 0.4 kV, power factor = 1

8) With a tolerance of + 5 %

9) Lower emission engines are available, consult Guascor Energy for performance data

Data is for continuous rating, at sea level, and at an ambient temperature of 77F (25°C)

Data for special gas and dual gas operation on request.

The values given in this data sheet are for information purposes only and not binding.

G-24HM & G-42HM

System Parameters	English Units	Metric Units	G-24HM				G-42HM			
Jacket (HT) water temperature max.	°F	°C	194	(90)	194	(90)	194	(90)	194	(90)
Jacket(HT) water flow rate min.	gpm	m³/h	145	(33)	128	(29)	167	(57)	181	(41)
Jacket (HT) water flow rate max.	gpm	m³/h	264	(60)	264	(60)	308	(70)	308	(70)
Intercooler stages			Single				Double			
Intercooler (LT) coolant temperature	°F	°C	131	(55)	131	(55)	131	(55)	131	(55)
Intercooler (LT) coolant flow rate min.	gpm	m³/h	88	(20)	110	(25)	88	(20)	110	(25)
Intercooler (LT) coolant flow rate max.	gpm	m³/h	132	(30)	132	(30)	132	(30)	132	(30)
Exhaust manifold type			Dry				Dry			
Exhaust temperature	°F	°C	914	(490)	905	(485)	792	(422)	851	(455)
Exhaust mass flow wet	lbs/hr	kg/h	4,519	(2,050)	5,512	(2,500)	10,891	(4,940)	11,067	(5,020)
Exhaust backpressure max.	psi	mbar	0.65	(45)	0.65	(45)	0.65	(45)	0.65	(45)
Maximum pressure loss in front of air cleaner	psi	mbar	0.073	(5)	0.073	(5)	0.073	(5)	0.073	(5)
Fuel pressure range	psi	mbar	0.73 - 3.48 (50 - 240)				0.73 - 3.48 (50 - 240)			
Starter battery 2x12 V, capacity required		Ampere-hour	280				280			
Emissions ⁹⁾	English Units	Metric Units	G-24HM				SGE-42HM			
NOx	g/bhp.hr	mg/Nm3	< 1 / <500		< 1 / 500		< 1 / 500		< 1 / 500	
CO	g/bhp.hr	mg/Nm3	< 2.2 / 1100		< 2.2 / 1100		< 2 / 1000		< 2 / <1000	
THC (in C1base)	g/bhp.hr	mg/Nm3	< 3,8 / 1900		< 3,8 / 1900		< 3,8 / 1900		< 3,8 / 1900	
NMHC (in C1 base)	g/bhp.hr	mg/Nm3	< 0.6 / <300		< 0.6 / <300		< 0.6 / <300		< 0.6 / <300	

1) Natural Gas MN80. For other MN consult Guascor Energy

2) Engine performance data acc. to ISO 3046/1

3) Assumes intake air flow at delta T = 5°C including combustion air

4) Not Including pipes and heat exchangers

5) Mean lube oil consumption between maintenance steps

6) At 60 Hz, U = 0.48 kV, power factor = 1

7) At 50 Hz, U = 0.4 kV, power factor = 1

8) With a tolerance of + 5 %

9) Lower emission engines are available, consult Guascor Energy for performance data

Data is for continuous rating, at sea level, and at an ambient temperature of 77F (25°C)

Data for special gas and dual gas operation on request.

The values given in this data sheet are for information purposes only and not binding.

G-56HM

Engine Parameters ²⁾	English Units	Metric Units	G-56HM					
			1,200		1,500		1,800	
Speed		rpm						
Engine power ²⁾	bhp	kWb	1,395	(1,040)	1,840	(1,373)	1,810	(1,350)
Cylinder arrangement			V16					
Mean effective pressure	psi	Bar	268	(18.5)	284	(19.6)	232	(16.0)
Bore	inch	mm	6.30	(160)	6.30	(160)	6.30	(160)
Stroke	inch	mm	6.89	(175)	6.89	(175)	6.89	(175)
Displacement	cu.in	litres	3,436	(56.3)	3,436	(56.3)	3,436	(56.3)
Mean piston speed	in/s	m/s	276	(7.0)	344	(8.8)	413	(10.5)
Compression ratio			11.9 : 1					
Combustion air mass flow	lbs/hr	kg/h	10,847	(4,920)	13,822	(6,270)	13,955	(6,330)
Packaged ventilation air flow ³⁾	scfm	m ³ /h	42,849	(72,800)	55,621	(94,500)	55,621	(94,500)
Engine coolant capacity (Main circuit) ⁴⁾	gal.	litres	69	(260)	69	(260)	69	(260)
Engine coolant capacity (Aux. circuit) ⁴⁾	gal.	litres	20	(75)	20	(75)	20	(75)
Lube oil capacity ⁵⁾	gal.	litres	111	(419)	111	(419)	111	(419)
Lube oil consumption ⁵⁾	lbs/bhp.hr	g/kWh	0.00025	(0.15)	0.00025	(0.15)	0.00025	(0.15)

1) Natural Gas MN80. For other MN consult Guascor Energy

2) Engine performance data acc. to ISO 3046/1

3) Assumes intake air flow at delta T = 5°C including combustion air

4) Not including pipes and heat exchangers

5) Mean lube oil consumption between maintenance steps

6) At 60 Hz, U = 0.48 kV, power factor = 1

7) At 50 Hz, U = 0.4 kV, power factor = 1

8) With a tolerance of + 5 %

9) Lower emission engines are available, consult Guascor Energy for performance data

Data is for continuous rating, at sea level, and at an ambient temperature of 77F (25°C)

Data for special gas and dual gas operation on request.

The values given in this data sheet are for information purposes only and not binding.

G-56HM

Energy Balance	English Units	Metric Units	G-56HM					
Generator efficiency ^{6) 7)}	%	%	97.2		97.3		96.8	
Electrical power ^{6) 7)}	kWe	kWe	1,011		1,337		1,307	
Jacket (HT) water heat	Btu x 1,000/hr	kW	2,035.0	(596)	2,445	(716)	2,448.1	(717)
Intercooler (LT) water heat	Btu x 1,000/hr	kW	198.0	(58)	362	(106)	283.4	(83)
Exhaust heat - cooled to 120°C	Btu x 1,000/hr	kW	1,591.1	(466)	2,042	(598)	2,506.2	(734)
Engine radiation heat	Btu x 1,000/hr	kW	225.4	(66)	300	(88)	286.8	(84)
Generator radiation heat	Btu x 1,000/hr	kW	99.4	(29)	119.8	(35)	147.5	(43)
Fuel consumption ⁸⁾	Btu x 1,000/hr	kW	8,126.3	(2,380)	10,509	(3,078)	10,816.9	(3,168)
Mechanical efficiency	%		43.7		44.6		42.6	
Electrical efficiency	%		42.5		43.4		41.3	
Thermal efficiency	%		47.1		46.1		48.4	
Total efficiency	%		89.5		89.5		89.7	

1) Natural Gas MN80. For other MN consult Guascor Energy

2) Engine performance data acc. to ISO 3046/1

3) Assumes intake air flow at delta T = 5°C including combustion air

4) Not including pipes and heat exchangers

5) Mean lube oil consumption between maintenance steps

6) At 60 Hz, U = 0.48 kV, power factor = 1

7) At 50 Hz, U = 0.4 kV, power factor = 1

8) With a tolerance of + 5 %

9) Lower emission engines are available, consult Guascor Energy for performance data

Data is for continuous rating, at sea level, and at an ambient temperature of 77F (25°C)

Data for special gas and dual gas operation on request.

The values given in this data sheet are for information purposes only and not binding.

G-56HM

System Parameters	English Units	Metric Units	G-56HM					
Jacket (HT) water temperature max.	°F	°C	194	(90)	194	(90)	194	(90)
Jacket(HT) water flow rate min.	gpm	m ³ /h	181	(41)	220	(50)	220	(50)
Jacket (HT) water flow rate max.	gpm	m ³ /h	308	(70)	308	(70)	308	(70)
Intercooler stages			Double					
Intercooler (LT) coolant temperature	°F	°C	131	(55)	104	(40)	131	(55)
Intercooler (LT) coolant flow rate min.	gpm	m ³ /h	66	(15)	88	(20)	110	(25)
Intercooler (LT) coolant flow rate max.	gpm	m ³ /h	132	(30)	132	(30)	132	(30)
Exhaust manifold type			Dry					
Exhaust temperature	°F	°C	763	(406)	766	(408)	878	(470)
Exhaust mass flow wet	lbs/hr	kg/h	11,222	(5,090)	14,307	(6,490)	14,462	(6,560)
Exhaust backpressure max.	psi	mbar	0.65	(45)	0.65	(45)	0.65	(45)
Maximum pressure loss in front of air cleaner	psi	mbar	0.073	(5)	0.073	(5)	0.073	(5)
Fuel pressure range	psi	mbar	0.73 - 3.48 (50 - 240)					
Starter battery 2x12 V, capacity required	Ampere-hour		280					
Emissions ⁹⁾	English Units	Metric Units	G-56HM					
NOx	g/bhp.hr	mg/Nm ³	< 1 / <500		< 1 / <500		< 1 / <500	
CO	g/bhp.hr	mg/Nm ³	< 2 / 1000		< 2 / 1000		< 2 / 1000	
THC (in C1base)	g/bhp.hr	mg/Nm ³	<3.8 / 1900		< 5.3 / 2650		<3.8 / 1900	
NMHC (in C1 base)	g/bhp.hr	mg/Nm ³	< 0.6 / 300		< 0.9 / 450		< 0.6 / 300	

1) Natural Gas MN80. For other MN consult Guascor Energy

2) Engine performance data acc. to ISO 3046/1

3) Assumes intake air flow at delta T = 5°C including combustion air

4) Not Including pipes and heat exchangers

5) Mean lube oil consumption between maintenance steps

6) At 60 Hz, U = 0.48 kV, power factor = 1

7) At 50 Hz, U = 0.4 kV, power factor = 1

8) With a tolerance of + 5 %

9) Lower emission engines are available, consult Guascor Energy for performance data

Data is for continuous rating, at sea level, and at an ambient temperature of 77F (25°C)

Data for special gas and dual gas operation on request.

The values given in this data sheet are for information purposes only and not binding.

Dimensions and other data

Engine Dimensions	English Units	Metric Units	G-24HM		G-42HM		G-56HM	
Width	in.	mm	81,850	(2,079)	84,843	(2,155)	84,291	(2,141)
Length	in.	mm	126,890	(3,223)	140,591	(3,571)	159,095	(4,041)
Height	in.	mm	62,598	(1,590)	85,866	(2,181)	87,284	(2,217)
Dry weight	lb	kg	9,259	(4,200)	13,779	(6,250)	16,535	(7,500)

Genset Dimensions	English Units	Metric Units	G-24HM		G-42HM		G-56HM	
Width	in.	mm	81,850	(2,079)	84,843	(2,155)	84,291	(2,141)
Length	in.	mm	155,591	(3,952)	191,536	(4,865)	218,307	(5,545)
Height	in.	mm	68,425	(1,738)	93,425	(2,373)	91,299	(2,319)
Dry weight	lb	kg	13,735	(6,230)	23,667	(10,735)	26,896	(12,200)

Noise emissions*

Engine Noise dB(A)	HZ (Frec. Band)	G-24HM		G-42HM		G-56HM		
		1,500	1,800	1,500	1,800	1,200	1,500	1,800
	125	73	67	71	-	71	73	70
	250	83	77	81	74	77	83	84
	500	85	80	84	88	79	85	82
	1,000	88	88	87	83	81	88	86
	2,000	92	91	90	90	88	92	92
	4,000	89	87	89	87	83	89	88
	LpA, ā dB(A)	96	94	94	94	90	96	95

Dimensions and other data

Noise emissions*

Exhaust Noise dB(A)	HZ	G-24HM		G-42HM		G-56HM		
	63	100	102	105	106	99	101	103
	125	121	131	119	129	109	122	125
	250	129	133	129	133	115	128	136
	500	116	122	116	123	116	122	127
	1,000	116	119	115	117	114	119	121
	2,000	115	117	113	114	114	117	117
	4,000	112	110	111	111	116	112	113
	LpA, \bar{a} dB(A)	130	136	130	135	122	130	137

Notes: Data obtained according to ISO 9614-2 • Data obtained @ 1 m from engine according to UNE-EN ISO-11203:1996
Maximum data standard deviations = ± 4 dB(A)



Published by Guascor Energy

Oikia, 44
20759 Zumaia (Gipuzkoa) Spain
PO Box 30
Tel: (Int'l +34) 943 86 52 00
Fax: (Int'l +34) 943 86 52 10



www.guascor-energy.com

Subject to changes and errors. The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. The requested performance features are binding only when they are expressly agreed upon in the concluded contract.

© Guascor Energy 2022

Guascor Energy is a trademark licensed by Guascor Energy S.A.U

Authorized Distributor



Kraft Power Corporation

199 Wildwood Ave
Woburn, MA 01801-2024
Tel: 315.898.8675
Email: CHP@kraftpower.com



<http://kraftpower.com/guascor-engines/>